



TECHNICAL DATASHEET

RSG F SERIES PARTICULATE RESPIRATORS

Discription

Easily applied cup shaped and flat fold styled disposable respirators. Both single use face masks are available with and without an exhalation valve.

The RSG filtering face pieces and particulate respirators meet the European Standard EN149:2001 + A1:2009 in FFP1, FFP2, and FFP3 classes of particulate filter efficiency. RSG **maintenance free single use filtering respirators** provide cost effective respiratory protection in hazardous workplaces and laboratories across a wide range of industries.

- The respirator provides effective filtration with low breathing resistance for consistent high quality performance
- Dolomite dust test provides proven protection and comfort for a minimum of 8 hours.
- Collapse resistant; ideal for work in warm and humid environments.
- Stays securely in place - thus helping to provide a good, comfortable seal.
- Soft foaming on the inside of the mask feels comfortable on the skin.
- Specially designed nose clip which keeps its flexibility even after prolonged usage and fits any nose shape or size.
- Elastic cotton headbands do not cause skin irritation and will not lose flexibility or pressure in hot or cold working conditions.
- RSG Butterfly exhalation valve offers the lowest breathing resistance and improved comfort in hot humid environments and/or where work is hard and physical.
- Comfortable and easy to use for workers with a wide variety of work security equipment such as helmets, safety glasses, ear plugs etc.
- Extremely lightweight.

Aproval

These products comply with the EU 2016/425 Regulation for Personal Protective Equipment and are thus CE marked.

Product approval by: IFA Sankt Augustin; Germany– Notified Body number 0121

Production Control 11A: IFA FA Sankt Augustin; Germany -Notified Body number 0121

Marking on the product: EN149:2001+A1:2009 CE0121

Standards

These products meet the requirements of recently amended European Standard EN 149:2001 + A1:2009, filtering facepiece respirators for use against particles. They should be used to protect the wearer from solid and non-volatile liquid particles only.

Products are classified by filtering efficiency and maximum total inward leakage performance (FFP1, FFP2 and FFP3), also by usability and clogging resistance.

Performance tests in this standard include filter penetration; extended exposure (loading) test; flammability; breathing resistance and total inward leakage. Reusable products are also subjected to cleaning, storage and mandatory clogging resistance tests (clogging is optional for non reusable products). A full copy of EN 149:2001+A1:2009 can be purchased from your national standards body.



TECHNICAL DATASHEET RSG F SERIES PARTICULATE RESPIRATORS

Designations:

- R = Reusable
- NR = Non reusable (single shift use only)
- D = Meets the clogging resistance requirements
- OV = Odor and vapors < OEL value

Applications

These respirators are suitable for use in concentrations of solid and non-volatile liquid particles up to the following limits:

Model EN 149:2001+A1:2009	Classification	Exhalation Valve	Nominal Protection Factor
200425	FFP1 NR D	No	4
200528 OV	FFP2 NR D	Yes	12
200529 OV (Welding FR)	FFP2 NR D + Ozone	Yes	12
200230	FFP3 NR D	Yes	50

200529 FFP2NR D Welding mask is made from a flame retardant outer shell to protect against welding sparks.

Materials

- Straps Elastic cotton textile
- Nose Foam Polyurethane
- Nose Clip Aluminium
- Filter Polypropylene
- Valve Polypropylene
- Valve diaphragm Thermoplastic Elastomer

These products do not contain components made from natural rubber latex.

Maximum mass of products:

- 200425 = 10g
- 200528 = 10g
- 200529 = 15g
- 200430 = 20g

Fitting Instructions

See Figure 1.

Before fitting device, ensure hands are clean. All respirator components should be inspected for damage prior to each use.





TECHNICAL DATASHEET

RSG F SERIES PARTICULATE RESPIRATORS

1. Hold the respirator in hand with the nosepiece at your fingertips. Allow headbands to hang freely below hand.
2. Cup the respirator firmly against your face with the nosepiece on the bridge of your nose.
3. Stretch and pull the lower headband over the head and position below your ears. Stretch and pull the top headband on the back of your head above your ears
4. Press soft nosepiece to conform snugly around the nose.
5. To test fit for respirator without exhalation valve: cup both hands over the respirator and inhale sharply. A negative pressure should be felt inside respirator. If air flows around your nose, tighten the nosepiece. If air leaks around the edges, reposition the headband for better fit.

Fit check

1. Cover the front of the respirator with both hands being careful not to disturb the fit of the respirator.
 - (a) UNVALVED respirator - EXHALE sharply;
 - (b) VALVED respirator - INHALE sharply.
2. If air leaks around the nose, re-adjust the nose clip to eliminate leakage. Repeat the above fit check.
3. If air leaks at the respirator edges, work the straps back along the sides of the head to eliminate leakage. Repeat the above fit check.

If you CANNOT achieve a proper fit DO NOT enter the hazardous area. See your supervisor. Users should be fit tested in accordance with national requirements.

For information regarding fit testing procedures, please contact RSG Safety BV: www.rsgsafety.com

Storage & Transportation

The RSG C Series Particulate Respirators have a shelf life of 5 years. End of shelf life is marked on the product packaging. Product should be stored in clean, dry conditions within the temperature range: – 5°C to + 25°C with a maximum relative humidity of <80%. When storing or transporting this product use original packaging provided.

Disposal

Contaminated products should be disposed as hazardous waste in accordance with national regulations.

Warnings & Limitations

Always be sure that the complete product is:

- Suitable for the application;
- Fitted correctly;
- Worn during all periods of exposure;
- Replaced when necessary.
- Proper selection, training, use and appropriate maintenance are essential in order for the product to help protect the wearer from certain airborne contaminants.



TECHNICAL DATASHEET RSG F SERIES PARTICULATE RESPIRATORS

- Failure to follow all instructions on the use of these respiratory protection products and/or failure to properly wear the complete product during all periods of exposure may adversely affect the wearer's health, lead to severe or life threatening illness or permanent disability.
- For suitability and proper use follow local regulations, refer to all information supplied or contact a safety professional/RSG Safety BV: www.rsgsafety.com.
- Before use, the wearer must be trained in use of the complete product in accordance with applicable Health and Safety standards/guidance.
- These products do not contain components made from natural rubber latex.
- These products do not protect against gases/vapours.
- Do not use in atmospheres containing less than 19.5% oxygen. Note: Individual countries may apply their own limits on oxygen deficiency. Seek advice if in doubt.
- Do not use for respiratory protection against atmospheric contaminants/concentrations which are unknown or immediately dangerous to life and health (IDLH).
- Do not use with beards or other facial hair that may inhibit contact between the face and the product thus preventing a good seal.
- Leave the contaminated area immediately if:
 - Breathing becomes difficult.
 - Dizziness or other distress occurs.
- Discard and replace the respirator if it becomes damaged, breathing resistance becomes excessive or at the end of the shift.
- Do not alter, modify, clean or repair this respirator.
- In case of intended use in explosive atmospheres, contact RSG Safety BV: www.rsgsafety.com
- Before initial use, always check that the product is within the stated shelf life (use by date).

Respirators Range



200425



200430



200528



200529